

» CG1200 Carrier Grade Server «



Intel® Xeon® Single or Dual 8-Core Processor E5-2448L
Intel® C600 Series Chipset

- » Dual 8 Cores with Hyperthreading (32 threads total)
- » Up to 8 slot, 3 channel support of DDR3/LVDDR3 RDIMM/UDIMM; supports 128GB maximum (with 16GB DIMM);
- » Optimized for Gen3 PCI-E IO card implementation with 1x PCI-e x16 riser (FH/ HL card3 - configuration dependent); Intel I/O module option
- » Up to four hot-swappable 2.5" SAS HDDs/SATA SSDs; integrated SAS/SATA interface with SW RAID 0/1/10
- » Dual redundant AC/DC hot-swappable power supplies
- » Support for Intel® Server Management Software
- » OS support: RedHat EL 6.2 (EM64T); SuSE SLES 11.2 (EM64T); Wind River Linux 3.0; Windows 2008 Server (EM64T)
- » Telco alarm support

CORPORATE OFFICES**Europe, Middle East & Africa**

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany

Tel.: +49 (0) 821 4086-0
Fax: +49 (0) 821 4086 111
sales@kontron.com

North America

14118 Stowe Drive
Poway, CA 92064-7147
USA

Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

Asia Pacific

17 Building,Block #1, ABP.
188 Southern West 4th Ring Road
Beijing 100070, P.R.China

Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn