
CRTtoLCD-1-TC/LC

Analog Flat-Panel-Controller with integrated Touch Controller (opt.)



- for easy Plug & Display connections of flatpanels to analog RGB-Video-sources
- newest chip-technology by Genesis gmZAN2 with full scaling capabilities (VGA up to SXGA)
- flatpanel-configuration via Serial-OSD (Windows Application) or keypad
- touch controller (only TC-Model)
 - ➤ 4/8 wire resistive touch technology
 - USB or PS2 connector




Product Overview

The CRTtoLCD-1-TC/LC is a highly integrated TFT flat panel interface adapter that allows to connect analog, 15 pin RGB sources with TFT panels. From a single 12 V power supply, the CRTtoLCD-1-TC/LC generates all the voltages required by a TFT panel and includes power sequencing features. The highly flexible architecture of the CRTtoLCD-1-TC/LC panel interface allows it to adapt to virtually any TFT panel. By an integrated Touch Controller the board incorporates all needed functionality to support 4/8 wire resistive Touch Panels (only CRTtoLCD-1-TC).

Save the money for an external Touch Controller! Typical Applications: Point of Sales (POS), Point of Information (POI), Gaming, Machines etc., Industrial Environment with VGA (15-Pin) and Touch Controller.

... We Drive Your Display!



➤ Technical Data

Easy connection of TFTs to a standard analog RGB VGA-interface:

- Highest quality up to SXGA (with full scaling capabilities)
- one product for different resolutions
- Newest chip-technology by Genesis gmZAN2

Analog-Input Features:

- Analog RGB VGA up to SXGA 70Hz
- 15 Pin standard VGA connector
- All color depths up to 24-bits/pixel are supported

Touch Features (only CRTtoLCD-1-TC):

- supports resistive Touch Panels
- 4/8 Wire, USB/PS2 Connectors

High-Quality Advanced Scaling:

> High quality

On-Screen Display:

- 5 button Keyboard
- On Screen Display (OSD) control for all features
- Serial OSD (Windows Application) via RS232

Display Interfaces:

- Digital RGB panel interface up to 18-Bit (FLEX32)
- Digital RGB panel interface up to 2x18-Bit (FLEX50)
- or LVDS panel interface (JILI40, one and double port up to 24 Bit)
- backlight dimming support

Operating Features:

- Single voltage supply (+12V DC)
- Dimension: width 95 mm, length 118,6 mm

Wide range of display cables is available under www.kontron-hhcom (see "Flatpanel Configurator")

Ordering Information	PartNo.	Description
CRTtoLCD-1-TC	21071	analog Flatpanel-Controller with analog RGB (15 Pin) Input and
		Touch-Controller with PS2-Connector (for digital TFT-Panels)
CRTtoLCD-1-TC	21075	same as 21071 but with USB-Connector
CRTtoLCD-1-TC	21072	analog Flatpanel-Controller with analog RGB (15 Pin) Input and
		Touch-Controller with PS2-Connector (for LVDS®-TFT-Panels)
CRTtoLCD-1-TC	21076	same as 21072 but with USB-Connector
CRTtoLCD-1-LC	21073	analog Flatpanel-Controller with analog RGB input (TTL)
CRTtoLCD-1-LC	21074	analog Flatpanel-Controller with analog RGB input (LVDS)

Corporate Offices

Europe, Middle East & Africa Marschnerstieg 7 22081 Hamburg - Germany

Tel.: +49 (40) 200090- 0 Fax: +49 (40) 200090- 10 www.kontron-hh.de sales-graphic@kontron.com US/ Canada 6260 Sequence Drive San Diego, CA 92121-4371

San Diego, CA 92121-437

Tel.: (858) 677-0877 Fax: (858) 677-0898

sales@us.kontron.com

Tel: +886 2 2781 5791 Fax: +886 2 2741 7379

Rd, Taipei, Taiwan

5F-1, 341, Sec 4, Chung Hsiao E.

sales@kontron.com.tw

Asia Pacific

