

CP-ASM3



Ready available 3U CompactPCI® card cages

- ▶ 19" racks with RIO and FAN options
- ▶ Industrial power supplies from 14 VDC to 260 VAC
- ▶ Backplanes with 2 to 8 slots segments
- ▶ EMI protected and CE compliant

POSSIBILITIES START HERE



CP-ASM3 is a series of ready integrated standard card cages for 3U CompactPCI®, based on the quality and experience of the technology leader. CompactPCI® is the most accepted modular standard throughout the ICT market segments. CompactPCI® is loved for any application, where openness, modularity, robustness, reliability, or longevity is an advantage. It provides outstanding.

- ▶ **Flexibility:** just plug another I/O board where needed
- ▶ **Variability:** upgrade to another CPU for higher performance
- ▶ **Longevity:** switch over to next generation CPU blade
- ▶ **Supplier-independency:** for special needs, select any market available component

▶ TECHNICAL INFORMATION

DIMENSIONS	84HP RACK 42HP RACK 84HP FAN TRAY 42HP FAN TRAY	483 x 133 x 282 mm / 84HP, 3U, 275 mm 220 x 133 x 242 mm / 42HP, 3U, 235 mm 483 x 45 x 282 mm / 84HP, 1U, 275 mm 220 x 45 x 242 mm / 42HP, 1U, 235 mm
P47-STYLE POWER SUPPLY	200 WATT AC	CP3-SVE-P200AC - Input: 85-264 VAC - Max Output: 5 V/40 A, 3.3 V/40 A, +12 V/5.5 A, -12 V/1.5 A. - Dimension: 3U, 8HP - Cooling: Forced airflow mandatory! - Characteristics: Hot swappable, redundant
	200 WATT DC 36 - 75 VDC	CP3-SVE-P200DC - Input: 36 - 75 VDC - Max Output: 5 V/40 A, 3.3 V/40 A, +12 V/5.5 A, -12 V/1.5 A. - Dimension: 3U, 8HP - Cooling: Forced airflow mandatory! - Characteristics: Hot swappable, redundant
	200 WATT DC 18 - 36 VDC	CP3-SVE-P200DC - Input: 18-36 VDC - Max Output: 5 V/25 A, 3.3 V/36 A, +12 V/3 A, -12 V/0.5 A - Dimension: 3U, 8HP - Cooling: Forced airflow mandatory! - Characteristics: Hot swappable, redundant
M-STYLE POWER SUPPLY	180 WATT AC	CP3-SVE-M180AC - Input: 85-264 VAC - Max Output: 5 V/20 A, 3.3 V/14 A, +12 V/2 A, -12 V/1 A. - Dimension: 3U, 12HP - Cooling: Free convection airflow - Characteristics: Not hot swappable, not redundant
	100 WATT DC	CP3-SVE-M100DC - Input: 14,4-154 - Max Output: 5V/10A, 3.3V/12A, +12V/9A - Dimension: 3U, 12HP - Cooling: Free convection airflow - Characteristics: Extended temperature, conformal coating, EN50155

For further information refer to the respective manuals of the power supplies or CompactPCI® backplanes.



// CP-ASM4R-84F-P200AC-B0800-STD

► TECHNICAL INFORMATION

COMPACTPCI® BACKPLANE	<p>FOR P47 STYLE PSU</p> <p>FOR M-STYLE PSU</p>	<p>CP3-BP8-P47-RIO</p> <ul style="list-style-type: none"> - PSU connector: P47 - Slot: 8, all 32 bit with Rear I/O right - System slot: <p>CP3-BP8-M-RIO</p> <ul style="list-style-type: none"> - PSU connector: M-style - Slot: 8, all 32 bit with Rear I/O right - System slot:
1U FAN TRAY	<p>84HP / 1U-275MM / 3.6W</p> <p>84HP / 1U-275MM / 15W</p> <p>42HP / 1U-235MM / 1.2W</p> <p>42HP / 1U-235MM / 5.6W</p>	<p>CP-MKIT-FAN-84-3</p> <ul style="list-style-type: none"> - Power consumption: 12 VDC / 3x 1.2 Watt - Airflow: 3x 95 m³/h (56cfm) / average of 1.25 m/s (250lfm) <p>CP-MKIT-FAN-84-15</p> <ul style="list-style-type: none"> - Power consumption: 12 VDC / 3x 5 Watt - Airflow: 3x 170 m³/h (100cfm) / average of 2.5 m/s (500lfm) <p>CP-MKIT-FAN-42-1</p> <ul style="list-style-type: none"> - Power consumption: 12 VDC / 1x 1.2 Watt - Airflow: 1x 95 m³/h (56cfm) / average of 0.8 m/s (160lfm) <p>CP-MKIT-FAN-42-5</p> <ul style="list-style-type: none"> - Power consumption: 12 VDC / 4x 1.4 Watt - Airflow: 4x 56 m³/h (33cfm) / average of 1.1 m/s (220lfm)
DISK DRIVE ASSEMBLY KITS	<p>SINGLE 2.5" SATA HDD/SSD</p> <p>DOUBLE 2.5" SATA HDD/SSD</p>	<p>CP-HDD-S-KIT-S</p> <p>CP-HDD-S-KIT-D</p>
GENERAL*	<p>AMBIENT TEMPERATURE</p> <p>HUMIDITY</p> <p>PROTECTION</p> <p>OVER VOLTAGE CATAGORY</p> <p>PROTECTION CLASS</p> <p>EMI</p> <p>SAFETY</p>	<p>0 °C to +50 °C</p> <p>Up to 93 % RH at 40 °C, non-condensing (acc. To IEC 60068-2-78)</p> <p>IP20</p> <p>2</p> <p>1</p> <p>EN55022 / EN55024</p> <p>EN60950-1</p>

* All systems described in the ordering list are conform to or better than.



// CP-ASM3R-84-M100DCWV-B0800-STD

▶ ORDERING INFORMATION

ARTICLE *	DESCRIPTION
COMPACTPCI® CARD CAGE 84HP	
CP-ASM3R-84-P200AC-B0800-STD CP-ASM4R-84F-P200AC-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, P47-style 200 Watt AC PSU and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3R-84-P200DC48V-B0800-STD CP-ASM4R-84F-P200DC48V-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, P47-style 200 Watt 48VDC PSU and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3R-84-P200DC24V-B0800-STD CP-ASM4R-84F-P200DC24V-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, P47-style 200 Watt 24VDC PSU and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3R-84-M180AC-B0800-STD CP-ASM4R-84F-M180AC-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, M-style 180 Watt AC PSU and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3R-84-M100DCWV-B0800-STD CP-ASM4R-84F-M100DCWV-B0800-STD	3U CompactPCI® Rack with RIO option, 84HP, M-style 100 Watt wide range PSU 16.8-137.5 VDC operating and 8 slot backplane, 4U variant including 1U fantray
CP-ASM3-84 CP-ASM4-84F	Any kind of additional 3U and 4U customized rack assemblies on request
COMPACTPCI® CARD CAGE 42HP	
CP-ASM3-42 CP-ASM4-42F ...	Any kind of additional 3U and 4U customized rack assemblies on request
CP-ASM4R-44F-M180AC-B0500-STD-TT	4U CompactPCI® table top rack with RIO option and fans, 44HP, M-style 180 Watt AC PSU, 5 slot backplane
DISK DRIVE ASSEMBLY KITS	
CP-HDD-S-KIT-S	SATA HDD/SSD carrier, 1 slot backplane, SATA cable
CP-HDD-S-KIT-D	2x SATA HDD/SSD carrier, 2 slot backplane, 2x SATA cable
CP-MKIT-CDROM	CDROM Assembly Set, 5.25", 32HP Front

*Drives and CompactPCI® boards can be integrated on request. Additional customized rack variants on request.

Moreover: dedicated system platforms

Ask for your entire platform solution for 3U CompactPCI®, based on a CP-ASM3 rack variant and the right selection out of Kontron's rich CPU blade portfolio, including periphery which fulfills your I/O, storage and networking requirements. Optionally, you may perform the hardware integration yourself. Or, in order to fully concentrate on your application, you may leave the integration to Kontron, and consequently address the platform responsibility to Kontron, which includes co-operability, obsolescence, environmental and EMC criteria of the system.

Dedicated project management

As a global company, Kontron has knowledgeable teams to support you in your region. Through your local project manager you have worldwide access to immense specialist know-how. Your project manager guides you securely through the entire design-in process to productionready product by means of a precise gate project plan. This allows you to concentrate on your core business and still retain an overview and full control of development, documentation, and production, including unique test processes, systems and procedures.

▶ Global Headquarters

Kontron S&T AG

Lise-Meitner-Str. 3-5
86156 Augsburg, Germany
Tel.: + 49 821 4086 0
Fax: + 49 821 4086 111
info@kontron.com
www.kontron.com