


CPS3101



3U CPCI-S.0 CARRIER FOR 2.5" SATA HDD/SSD

- ▶ High-Speed Connectivity
- ▶ Service-Friendly Implementation
- ▶ Rugged Design


CPS3101

3U CPCI-S.0 CARRIER FOR 2.5" SATA HDD/SSD

The CPS3101 is a 3U CompactPCI® Serial carrier board that provides support for one 2.5" SATA HDD or SSD (transfer rates up to 6Gb/s are supported). In addition, the CPS3101 is equipped with an on-board USB 3.0 connector enabling the connection to system-internal USB devices.

To ensure maximum signal integrity, redriver components are used for the SATA and USB interfaces.

The complete board design is optimized for best shock and vibration resistance. Moreover, it offers customers a service-friendly implementation. Status information of the carrier board and the drive assembled are shown via four LEDs on the front panel. If a drive fails, the complete carrier board can be hot swapped during system operation.



TECHNICAL INFORMATION

FRONT INTERFACES	LEDS	<ul style="list-style-type: none"> - Act (Activity): Activity of the HDD/SSD - Loc (Locate): Locates the HDD/SSD in a RAID array - Fail (Error): Failure Status of the HDD/SSD - Pwr (Power): Power Status of the CPS3101
	HOT SWAP HANDLE	If the HS handle is pressed the onboard power supplies will be shut down and the board can be safely removed from the CPCI-S.0 system environment
ONBOARD INTERFACES	SATA USB	<ul style="list-style-type: none"> One SATA connector for connecting one 2.5" SATA HDD/SSD, SATA 6Gb/s One angled USB 3.0 connector, 9-pin type-A
COMPACTPCI SERIAL INTERFACE	CPCI-S.0 INTERFACE	<ul style="list-style-type: none"> - P1 connector supporting one SATA 6Gb/s, one USB 3.0 interface and the SGPIO bus - Option to assemble the P6 for increased mechanical stability
COMPLIANCY		<ul style="list-style-type: none"> - CompactPCI® Serial Specification PICMG® CPCI-S.0 R1.0 - Safety: compliant to IEC60950-1, EN60950-1, UL94-V0; designed to meet: UL60950-1, CSA 22.2 No. 60950-1 - EMC: compliant to EN55022 Class B, EN55024, EN61000-6-1/ -2/ -3 /-4, EN50121-3-2 (Railway); designed to meet: FCC, VCCI, BSMI
GENERAL	DIMENSIONS WEIGHT MTBF	<ul style="list-style-type: none"> 3U / 4HP, 100 x 160 mm 135 g 1,731,576 h acc. to MIL-HDBK-217 FN2, Ground Benign, controlled at 30°C
ENVIRONMENTAL	OPERATING TEMPERATURE STORAGE TEMPERATURE CLIMATIC HUMIDITY	<ul style="list-style-type: none"> 0°C to +60°C standard, -40°C to +85°C extended temperature -40°C to +85°C (without additional components) 93% RH at 40°C, non-condensing (acc. to IEC 60068-2-78)

ORDERING INFORMATION

ARTICLE	DESCRIPTION
CPS3101	3U/4HP carrier board for one 2.5" SATA HDD/SSD, internal USB 3.0 connector

CORPORATE OFFICES

EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5
 86156 Augsburg
 Germany
 Tel.: + 49 821 4086 0
 Fax: + 49 821 4086 111
 info@kontron.com

NORTH AMERICA

14118 Stowe Drive
 Poway, CA 92064-7147
 USA
 Tel.: + 1 888 294 4558
 Fax: + 1 858 677 0898
 info@us.kontron.com

ASIA PACIFIC

1-2F, 10 Building, No. 8 Liangshuihe 2nd Street,
 Economical & Technological Development Zone,
 Beijing, 100176, P.R.China
 Tel.: +86 10 63751188
 Fax: +86 10 83682438
 info@kontron.cn