

AIRES 16x GbE RUGGED SWITCH



AIRES1600PDC0T1STD

- ▶ rugged, IP67 sealed system
- ▶ small form factor (1.75" H x 6.5" D x 8.5" W) and low power
- ▶ 16x GbE ports with individual connectors
- ▶ +28VDC power input for vehicle or aircraft
- ▶ -40C° to +71C° wide temperature range

POSSIBILITIES START HERE



kontron

AIRES 16x GbE RUGGED SWITCH

The AIRES product family extends Kontron's existing Ethernet switch portfolio and features a fully managed Layer 2/3 Gigabit Ethernet switch offering IPv4/IPv6 routing and full management capabilities. It supports a powerful set of CLI, Telnet, Web and SNMP management interfaces to configure the entire set of protocols and parameters including Layer 2 and Layer 3 (IPv4/IPv6) protocols, Multicasting, QoS and Security. The AIRES is uniquely designed and tested to survive in harsh and extreme environments conditions found in military, avionics, commercial avionics, mining, smart grid, homeland security, transportation (rail), and oil & gas markets.

UNIQUE VERSATILITY

A combination of port count, connector type, and power supply options ensure the highest connectivity and operational capability. The AIRES product family is available in many different front I/O versions and power supply options. The AIRES1600PDCOT1STD provides 16x GbE direct port connections using small and rugged connector solutions.

ROBUST AND RELIABLE

The rugged design, selection of high temperature components along with an optimized thermal solution ensures high product reliability. The AIRES product family is able to handle the toughest environmental conditions.

LONG-TERM AVAILABILITY

Based on chosen components from embedded roadmaps, the AIRES ensures long-term availability and therefore eliminates the risk of unplanned design changes and unexpected application modification.

KEY FEATURES OF AIRES1600PDCOT1STD

- ▶ Fully managed Layer 2 / 3 non blocking Ethernet Switch, IPv6 support
- ▶ 16x Port Connectors 10/100/1000BASE-T
- ▶ SNMP, command line and web management interface
- ▶ Small Form Factor & Low Power, 1.75"H x 6.5"D x 8.5"W
- ▶ +28VDC power input for vehicle or aircraft

TECHNICAL INFORMATION

CONTROLLER AND SWITCH	Broadcom BCM56333 or BCM56334 Ethernet switch PowerPC® 405EX, 32-bit, RISC processor core operating up to 600 MHz NXP LPC2368 32-bit microcontroller 512MB DDR2 RAM 200 MHz 1GB NAND Flash for file storage
SOFTWARE MANAGEMENT	Management via SNMP, Telnet, CLI - In-band - Out-of-band via Ethernet or RS232 Reliable software, field upgradable, Dual boot images with roll-back capabilities, Advanced management monitoring features
SOFTWARE SWITCHING & ROUTING	Ethernet Bridging: - Static and dynamic link aggregation, Classic, rapid and multiple spanning tree algorithms, Quality Of Service, Full Duplex operation and flow control, Layer 2 multicast services, VLAN support, Access Control Lists IP Routing: - IPv4 Forwarding, ARP, ICMP, static routing, OSPF and RIP routing, Virtual router redundancy protocol (VRRP), ECMP Equal Cost Multipath routing Multicast: - IP Multicasting, IGMPv2 /v3, PIM-DM/PM, DVMRP, MLD v1/v2, IGMP and MLP snooping Services: - SNMP client, DHCP server, Event Management, POST, SNMP, Support for multiple configurations, TFTP server, Power on and diagnostic tests
POWER INPUT	Integrated +28VDC input (+18VDC to +36VDC) power supply and EMI filtering supports MIL-STD-704, MIL-STD-461 and D0160, Optional External wide range AC power supply available for development
POWER CONSUMPTION	Less than 25W
OPERATING TEMPERATURE	-40C° to +71C°
SHOCK	40g, 11ms sawtooth
VIBRATION	5 Hz to 2000 Hz, Random, 1hr each axis, 8.21 GRMS Power Spectrum Density
EMI/RFI	FCC Part 15, RTCA/DO-160, MIL-STD-461, IEC 61000
HUMIDITY	95% non-condensing
SIZE	1.75" (44.5mm) H x 6.5" (165mm) D x 8.5" (216mm) W
WEIGHT	3.9lbs (1.7kg)
CONNECTOR	Military Circular locking connector IP67 rated. LAN 1 - LAN 16 single connector per GbE port with activity LED

CORPORATE OFFICES

EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5
86156 Augsburg
Germany
Tel.: +49 821 4086 0
Fax: +49 821 4086 111
info@kontron.com

NORTH AMERICA

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

ASIA PACIFIC

1-2F, 10 Building, No. 8 Liangshuihe 2nd Street,
Economical & Technological Development Zone,
Beijing, 100176, P.R.China
Tel.: +86 10 63751188
Fax: +86 10 83682438
info@kontron.cn