

➤ **KISS 4U PCI-960**

Kontron Industrial **S**ilent Server



Energy saving

Low Noise

Redundant

4U Open Solution

- Core™ Duo, Core™ 2 Duo
- Passiv Backplanes with up to 13 Slots
- Shock protected Drive bays
- RAID Subsystem KISS Stor 1 or KISS Stor 0/5
- PICMG 1.3

➤ Product Overview

KISS - 4U Kontron Industrial Silent Server The KISS system has been designed with flexibility in mind and can accommodate PICMG 1.0, PICMG 1.3, ATX and Dual Xeon/64-bit based motherboards, as well as PCI Express ATX motherboards, all in a case that can be used as a tower, desktop or 19" rack mounted chassis. The main attraction of KISS servers is their extremely low noise level: they are inaudible against normal conversation. KISS IPC servers are therefore ideal for most noise-sensitive environments, such as hospital operating theaters and computer server rooms. The performance and configuration of KISS servers are based on Kontron's extensive range of CPU boards and backplanes, which allows them to be adapted to meet a very wide range of requirements. Redundant PSUs, RAID Subsystem KISS Stor and Remote Diagnostic Software make KISS family a high reliable and contigious operating industrial Server. Extra accessories adapt KISS to precisely meet your specific requirements

➤ Technical Information

System	KISS 4U PCI-960
Product Line	KISS 4U
Dimension (H x W x D)	177 mm x 482 mm x 472 mm 4U x 19" x 18,58"
Weight	Approx. 15 kg
Interfaces Front	2 x USB 2.0
Interfaces of the installed board (rear)	2 x USB 2.0, 2 x LAN 10/100/1000, 1 x VGA, 2 x RS232
Controls on the frontside	ATX Switch, Reset
External accessible drive bays	3 x 5,25", 2 x 3,5", 1 x SLIM line
Internal drive bays	1 x 3,5"
Power supply	100-240 V AC 300 W optional AC 460 W, optional AC Redundant
Expansion slots	1 x PCI_e x 16, 4 x PCI_e x 1, 7 x PCI 32 Bit
Memory	Up to 4 GB DDR2

Processor	Celeron 440 (1 x 1,86 GHz) T2500 (2 x 2,0 GHz) T7400 (2 x 2,16 GHz)
Temperature	-20°C - +70°C, non-operating 0°C - +50°C, operating
Humidity	10-90 %, non-operating 20-90 %, operating
Shock	30g, 11ms, non-operating 15g, 11ms, operating
Vibration	1g 10-500 Hz, operating 2g 10-500 Hz, storage
Noise	< 35 dBA
Approvals	CE, designed to meets UL
MTBF	50.000 h
Protection Class	Front IP20
Options	DVD ROM, DVD R/W RAID Subsystem KISS Stor 1 or KISS Stor 0/5 Slide Rails, PC Condition Monitoring Software



➤ Corporate Offices

EMEA
Kontron AG
Oskar-von-Miller-Straße 1
85386 Eching

Tel: +49 (0)8165/77 0
Fax: +49 (0)8165/77 219
sales@kontron.com

NORTH AMERICA
Kontron America Corporate Office
14118 Stowe Drive
Poway CA, 92064-7147

Tel: (888) 294-4558
Fax: (858) 677-0898
sales@kontron.com

Asia Pacific
4F, No. 415, Ti-Ding Blvd.
Sec. 2, NeiHu District
Taipei, Taiwan 114

Tel: +886 2 2799 2789
Fax: +886 2 2799 7399
sales@kontron.com.tw