

# KISS 4U V2 KTQ67

---



## HIGH PERFORMANCE COMPUTER PLATFORM FOR CHALLENGING OR NOISE SENSITIVE ENVIRONMENTS

- ▶ low noise < 35 dBA
- ▶ rugged design - shock protected drive bays
- ▶ easy customization with modified standard (MoSt) concept
- ▶ predictable maintenance with remote diagnostic

POSSIBILITIES START HERE



**kontron**

## ► TECHNICAL INFORMATION

SYSTEM		KISS 4U V2 KTQ67
PRODUCT LINE		KISS 4U V2
DIMENSION (H X W X D)		177 x 482 x 472 mm (4U x 19" x 18.58")
WEIGHT		Approx. 15 kg
INTERFACES FRONT		2x USB 2.0
INTERFACES OF THE INSTALLED BOARD (REAR)		3x LAN 10/100/1000, 2x Displayport, 1x VGA, 2x COM, 6x USB, HD Audio
CONTROLS ON FRONTSIDE		Power button
EXTERNAL ACCESSIBLE DRIVE BAYS		3x 5,25", 1x 3,5"
INTERNAL DRIVE BAYS		1x 3.5"
POWER SUPPLY		AC 400 W 80+, optional: AC Redundant, DC 24 V, DC 48 V
EXPANSION SLOTS		5x PCI 32bits/33MHz, 1x PCIe x4 (In x16 connector), 1x PCIe x16
CPU BOARD		KTQ67ATXE
CHIPSET		Q67
MEMORY		Up to 16 GByte DDR 3
PROCESSOR		i3-2120, i5-2400, i7-2600
COOLING		Two hot swap chassis fans, air filter
TEMPERATURE	NON-OPERATING OPERATING	-20 °C to + 70 °C (-4 °F - 154 °F) 0 °C to + 50 °C (32 °F - 122 °F)
HUMIDITY	OPERATING/NON OPERATING	10-95 % rel humidity at 40 °C non condensing
SHOCK	OPERATING	15 g, 11 ms
VIBRATION	OPERATING	10-500 Hz, 1 g
NOISE		< 35 dBA
APPROVALS		CE
PROTECTION CLASS		IP 20 optional IP 52

## ► CORPORATE OFFICES

### EUROPE, MIDDLE EAST & AFRICA

Lise-Meitner-Str. 3-5  
86156 Augsburg  
Germany  
Tel.: + 49 821 4086 0  
Fax: + 49 821 4086 111  
info@kontron.com

### NORTH AMERICA

14118 Stowe Drive  
Poway, CA 92064-7147  
USA  
Tel.: + 1 888 294 4558  
Fax: + 1 858 677 0898  
info@us.kontron.com

### ASIA PACIFIC

1-2F, 10 Building, No. 8 Liangshuihe 2nd Street,  
Economical & Technological Development Zone,  
Beijing, 100176, P.R.China  
Tel.: +86 10 63751188  
Fax: +86 10 83682438  
info@kontron.cn