

Open Frame Development Chassis



6U/ 34 HP Backplanes

Open Frame Development Chassis

The open chassis is designed for test and development engineers, providing flexibility and ease of use. The chassis is designed for use with RTM boards, and offers easy access to boards from both sides. The rear profiles are moveable up to 2.5mm for using different RTM boards (cPCI, VME etc.).

The mechanical construction is very robust with 6mm/ .236" thick sidewalls. To ensure efficient cooling, 3 high performance fans are placed below the chassis, with front and rear air plenums to maximize air flow.

The Development chassis can be configured for various platforms, including VPX, VME, VME64x, cPCI, VXI, and VXS. Select from a wide range of backplanes from Hartmann Electronic. You can use backplanes up to a width of 34 HP.



Front view

Key features:

- Open architecture for easy access to boards from both sides
- For use with RTM boards
- very robust and strong construction, IEEE1101.10 card guides (Polycarbonate UL94-V0) and ESD clip mounted on bottom side
- excellent cooling from 3 high performance fans (12 V DC)
 - Fan front boards: one, 120 x 120 x 38mm, 224 CFM (39dB(A)), 0.48A
 - Fan RTM boards: two, 80 x 80 x 25mm, 38.8 CFM (34dB(A)), 0.23A
- adjustable rotary speed for front board cooling
- separate switch for rear fans
- front side switch
- LED voltage control front side
- LED fan control front side
- Industrial 300 W ATX power supply unit with wide range input 90–264V_{AC}
 - Output: 3.3V/ 28A, 5V/35A, 12V/22A, -12V/1A
 - min. load: 5V/0.5A, 12V/ 1A) with PFC, with fan and switch.
 - Other power supplies available on request!



Rear view

Open Frame Development Chassis



6U/ 34 HP Backplanes

1) Dimensions and Materials:

Height: 450 mm/ 17.72"

Width: 184.9 mm/ 7.28"

Depth: 302.1 mm/ 11.89"

Weight: 6.6 Kg/ 15 lbs


Extrusions, Top and Base: Aluminium DIN EN AW 5754 H22 G22

Side panels: 6mm/ .236" thick Aluminium, painted color red (RAL 3020 appr. FED-STD-595 Color No. 31400)


Operating Temperature: 0° - +50°C

Storage Temperature: -10°C - +60°C


Flammability rating: UL94-V0



Front view



Top view



Side view

2) Front Control board:

- Main power switch
- LED array for all voltages and fan/fail for front fan
- Front fan speed is adjustable
- Rear fans have a separate switch



3) Easy Configuration:

- Hinged front door for easy modifications
- Fast and easy access to power screw termination

Order number:

LMH0000452 for 3U backplanes

LMH0000462 for 6U backplanes

