

XtremeView

ULTRA-SLIM FRAME, FANLESS, ANTI-SPRAY



18.5" / 21.5" WIDESCREEN 10-POINT PCAP MULTI-TOUCH MONITOR

- ▶ 1x HDMI, 1x DVI-D, 1x VGA for video input
- ▶ 1x USB2.0 for touch functionality
- ▶ IP65-rated front design
- ▶ Fully flat front design without height gap
- ▶ Ultra-slim frame design

XtremeView

18.5" / 21.5" WIDESCREEN 10-POINT PCAP MONITOR



Kontron XtremeView is a widescreen monitor. It features 10-point PCAP multi-touch panel and enables fast / intuitive operation. Besides, it comes with a variety of display ports, including 1x HDMI, 1x DVI-D and 1x VGA, for various viewing options, and 1x USB 2.0 for touch functionality.

anti-scratch glass surface. It can thus protect against water spray intrusion, resist scratches / abrasion from sharp / rough stuff, and prevent the accumulation of visible or non-visible contamination on the surface. As a result, it is able to provide excellent resistance to harsh conditions and is highly suitable to a wide range of industrial applications.

The XtremeView has an IP65-rated fully flat front design and


▶ PRODUCT HIGHLIGHTS

- ▶ 18.5" / 21.5" widescreen 10-point PCAP multi-touch LCD display
- ▶ 1x HDMI, 1x DVI-D, 1x VGA for video input
- ▶ 1x USB 2.0 for touch functionality
- ▶ IP65-rated front design
- ▶ Fully flat front design without height gap
- ▶ Ultra-slim frame design
- ▶ Glass hardness of 6H



▶ MECHANICAL DIMENSIONS

▶ 18.5" Model



▶ 21.5" Model



▶ TECHNICAL INFORMATION

VIDEO	DISPLAY SIZE ASPECT RATIO BACKLIGHT RESOLUTION BRIGHTNESS (cd/m², typ.) CONTRAST RATIO (typ.) COLOR VIEWING ANGLE (L/R/H/L, °) TOUCH DISPLAY INTERFACE	18.5 inch 16:9 LED 1366 x 768 WXGA 300 1000:1 16.7M 85 / 85 / 80 / 80 10-point PCAP 1x HDMI (on rear) 1x DVI-D (on rear) 1x VGA (on rear)	21.5 inch 16:9 LED 1920 x 1080 Full HD 250 5000:1 16.7M 89 / 89 / 89 / 89 10-point PCAP
AUDIO	AUDIO INTERFACE	1x Line-in (on rear) 1x Line-out (on rear)	
TOUCH INTERFACE	USB	1x USB 2.0 (Type A on rear)	
POWER	INPUT VOLTAGE CONNECTOR	DC 9 V ~ 36 V 3-pin Phoenix Connector (on rear)	
SYSTEM CONTROL & MONITORING	BUTTON, SWITCH & INDICATOR	1x Power Button (on rear) 1x Power LED (on rear) 1x Menu / Enter Button (on rear) 1x Up Button (on rear) 1x Down Button (on rear) 1x Exit Button (on rear)	
COOLING	COOLING METHOD	Passive	
MECHANICAL	CONSTRUCTION DIMENSIONS - W DIMENSIONS - H DIMENSIONS - D WEIGHT MOUNTING	Glass Surface + Metal Chassis w/ Ultra-slim Frame 465.2 mm (18.31") 286.3 mm (11.27") 50.5 mm (1.99") TBD Panel Mount	
ENVIRONMENTAL	OPERATION TEMPERATURE STORAGE TEMPERATURE HUMIDITY	0 °C ~ 50 °C / 32 °F ~ 122 °F -20 °C ~ 80 °C / -4 °F ~ 176 °F 0 % ~ 95 %	
COMPLIANCE	INGRESS PROTECTION	IP65 (front)	

▶ ORDERING INFORMATION

ARTICLE	DESCRIPTION
XtremeView-185-P00	18.5" 16:9 10-point PCAP LCD Display
XtremeView-215-P00	21.5" 16:9 10-point PCAP LCD Display

ACCESSORIES	DESCRIPTION
ARTICLE	
POWER ADAPTER	Input: AC 100 V ~ 240 V, Output: DC 24 V, w/ terminal block
POWER CORD	EU / US / UK / JP / CN / AU type depending on country
PANEL MOUNT CLAMP	Mounting clamp screws (q'ty depending on panel size)

▶ PRODUCT CONTACT POINT

KONTRON ASIA INC.

4F, No. 415, Ti-Ding Blvd., Sec. 2,
Neihu District, Taipei, Taiwan 114741
Tel.: + 886 2 2799 2789
Fax: + 886 2 2799 7399
SalesAsia@kontron.com
www.kontron.com