



## **KISS 4U Short V2 Systems**

### **Configuration Guides**

This page is intentionally left blank.

Configuration Options for KISS 4U Short V2 with KTQ45/Flex		
Categories	Select one option of each category	
<b>Mainboard</b>	KTQ45/Flex	
<b>Processors</b>	Intel Core2 DUO E4300 1.8 GHz	
	Intel Core2 DUO E8400 3.0 GHz	
	Intel Core2 QUAD Q9400 2.66 GHz	
<b>Memory</b>	4GB DDR3 1333	
	8GB DDR3 1333	
<b>Drive Bay 1, 2</b>		1 2
<b>Front accessible 5.25"</b>	No	
	DVD-R/RW SATA 5.25	
	DA135 500GB	
	DA135 1TB	
	DA135 2TB	
	KISS-Stor 1 (2* 500 GB) (blocks two 5.25" Bays)	
	KISS-Stor 1 (2* 1TB) (blocks two 5.25" Bays)	
	KISS-Stor 1 (2* 2TB) (blocks two 5.25" Bays)	
	KISS-Stor 0/5 (3* 500 GB) (blocks two 5.25" Bays)	
	KISS-Stor 0/5 (3* 1TB) (blocks two 5.25" Bays)	
	KISS-Stor 0/5 (3* 2TB) (blocks two 5.25" Bays)	
	DA335 3x 500 GB	
	DA335 3x 1TB	
	DA335 3x 2TB	
	DA425 4x 250GB	
	DA425 4x 500GB	
<b>Drive Bay 3</b>		3
<b>Internal 3.5"</b>	No	
	SATA 500 GB	
	SATA 1TB	
	SATA 2TB	
	SSD 80 GB MLC (0-70°C)	
	SSD 120 GB MLC (0-70°C)	
	SSD 160 GB MLC (0-70°C)	
	Slim-line DVD R/RW	
<b>Power Supply</b>	AC 400 W (wide range)	
	DC 24V 300 W	
	DC 48V 300 W	
<b>Graphic Adapter</b>	No	
	Graphic card PCIe x16 passive Low profile	
<b>Network Adapter</b>	No	
	1* GB LAN PCIe x1	
	others on request	
<b>RAID Controller</b>	No	
	0, 1, 5, 10, JBOD PCIe x1	
<b>Options</b>	No	
	Custom Color	
	Slide Rails	
	PCCM	
	others on request	
<b>Preinstalled OS</b>	No	
	Windows XP Multilingual	
	Linux Suse	
	WIN 7 32 bit Professional	
	WIN 7 64 bit Ultimate	
	Others on request	
<b>Variant</b>	Desktop	
	19" Rack Mount	
<b>Protection Class</b>	Front: IP20	
	Front: IP52	

Configuration Options for KISS 4U Short V2 with KTQ67/Flex		
Categories	Select one option of each category	
<b>Mainboard</b>	KTQ 67/Flex	
<b>Processors</b>	Intel Core i3-2120 3.3 GHz	
	Intel Core i5-2400 3.1 GHz	
	Intel Core i7-2600 3.4 GHz	
<b>Memory</b>	4GB DDR3 1333	
	8GB DDR3 1333	
	16 GB DDR3 1333	
<b>Drive Bay 1, 2</b>		1 2
<b>Front accessible 5.25"</b>	No	
	DVD-R/RW SATA 5.25	
	DA135 500GB	
	DA135 1TB	
	DA135 2TB	
	KISS-Stor 1 (2* 500 GB) (blocks two 5.25" Bays)	
	KISS-Stor 1 (2* 1TB) (blocks two 5.25" Bays)	
	KISS-Stor 1 (2* 2TB) (blocks two 5.25" Bays)	
	KISS-Stor 0/5 (3* 500 GB) (blocks two 5.25" Bays)	
	KISS-Stor 0/5 (3* 1TB) (blocks two 5.25" Bays)	
	KISS-Stor 0/5 (3* 2TB) (blocks two 5.25" Bays)	
	DA335 3x 500 GB	
	DA335 3x 1TB	
	DA335 3x 2TB	
	DA425 4x 250GB	
	DA425 4x 500GB	
<b>Drive Bay 3</b>		3
<b>Internal 3.5"</b>	No	
	SATA 500 GB	
	SATA 1TB	
	SATA 2TB	
	SSD 80 GB MLC (0-70°C)	
	SSD 120 GB MLC (0-70°C)	
	SSD 160 GB MLC (0-70°C)	
	Slim-line DVD R/RW	
<b>Power Supply</b>	AC 400 W (wide range)	
	DC 24V 300 W	
	DC 48V 300 W	
<b>Graphic Adapter</b>	No	
	Graphic card PCIe x16 passive Low profile	
<b>Network Adapter</b>	No	
	1* GB LAN PCIe x1	
	others on request	
<b>RAID Controller</b>	No	
	0, 1, 5, 10, JBOD PCIe x1	
<b>Options</b>	No	
	Custom Color	
	Slide Rails	
	PCCM	
	others on request	
<b>Preinstalled OS</b>	No	
	Windows XP Multilingual	
	Linux Suse	
	WIN 7 32 bit Professional	
	WIN 7 64 bit Ultimate	
	Others on request	
<b>Variant</b>	Desktop	
	19" Rack Mount	
<b>Protection Class</b>	Front: IP20	
	Front: IP52	