

# KISS 4U Short Systems

## Configuration Guides



Configuration Options for KISS 4U Short with 886LCD-M/Flex			
Categories	Select one option of each category		
<b>Mainboard</b>			
	886LCD-M/Flex		
<b>Processors</b>			
	Celeron M 370 (1.5GHz)		
	Pentium M Dothan (1.8GHz)		
<b>Memory</b>			
	512MB DDR		
	1GB DDR		
	2GB DDR		
<b>Drive Bay 1, 2, 3</b>		1	2 3
<b>Front accessible 5.25"</b>	No		
	SATA 250 GB		
	SATA 500 GB		
	SATA 750 GB		
	SATA 1TB		
	KISS-Stor 1 (2* 250 GB) (blocks two 5.25" Bays)		
	KISS-Stor 1 (2* 500 GB) (blocks two 5.25" Bays)		
	KISS-Stor 1 (2* 750 GB) (blocks two 5.25" Bays)		
	KISS-Stor 1 (2* 1TB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 250 GB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 500 GB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 750 GB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 1TB) (blocks two 5.25" Bays)		
	DVD ROM PATA		
	DVD -R/RW PATA		
<b>Drive Bay 4</b>		4	
<b>Internal 3.5"</b>	No		
	SATA 250 GB		
	SATA 500 GB		
	SATA 750 GB		
	SATA 1TB		
	Slim-line CD-R/RW DVD-ROM		
<b>Power Supply</b>			
	AC 275W (115/230VAC)		
<b>Graphic Adapter</b>			
	No		
	AGP Matrox Mill. G550 DH 32 MB		
<b>Network Adapter</b>			
	No		
	PCI NET D-LINK DFE-528TX 10/100Mbps		
<b>Options</b>			
	No		
	Custom Color		
	Slide Rails		
	others on request		
<b>Preinstalled OS</b>			
	No		
	Windows XP Multilingual		
	Linux Suse		
	WIN 2003 SERVER		
	Others on request		
<b>Variant</b>			
	Desktop		
	19" Rack Mount		

Configuration Options for KISS 4U Short with 986LCD M/Flex			
Categories	Select one option of each category		
<b>Mainboard</b>	986LCD-M/Flex		
<b>Processors</b>	Celeron M 440 (1.86GHz)		
	Core™ Duo T2500 (2.0 GHz)		
	Core™ 2 Duo T7400 (2.16GHz)		
<b>Memory</b>	2GB DDR2		
	4GB DDR2		
<b>Drive Bay 1, 2, 3</b>		1	2 3
<b>Front accessible 5.25"</b>	No		
	SATA 250 GB		
	SATA 500 GB		
	SATA 750 GB		
	SATA 1TB		
	KISS-Stor 1 (2* 250 GB) (blocks two 5.25" Bays)		
	KISS-Stor 1 (2* 500 GB) (blocks two 5.25" Bays)		
	KISS-Stor 1 (2* 750 GB) (blocks two 5.25" Bays)		
	KISS-Stor 1 (2* 1TB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 250 GB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 500 GB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 750 GB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 1TB) (blocks two 5.25" Bays)		
	DVD ROM SATA		
	DVD -R/RW SATA		
<b>Drive Bay 4</b>		4	
<b>Internal 3.5"</b>	No		
	SATA 250 GB		
	SATA 500 GB		
	SATA 750 GB		
	SATA 1TB		
	Slim-line CD-R/RW DVD-ROM		
<b>Power Supply</b>	AC 275W (115/230VAC)		
<b>Graphic Adapter</b>	No		
	PCIe *16 GEF NX8500GT-TD256EH/D2		
<b>Network Adapter</b>	No		
	PCI NET D-LINK DFE-528TX 10/100Mbps		
<b>Options</b>	No		
	Custom Color		
	Slide rails		
	others on request		
<b>Preinstalled OS</b>	No		
	Windows XP Multilingual		
	Linux Suse		
	WIN 2003 SERVER		
	Others on request		
<b>Variant</b>	Tower		
	Desktop		
	19" Rack Mount		

Configuration Options for KISS 4U Short with KT965/Flex			
Categories	Select one option of each category		
<b>Processor boards</b>			
	KT965/Flex		
<b>Processors</b>			
	Core™ 2 Duo E4300 (1.8GHz)		
	Core™ 2 Duo E6400 (2.13GHz)		
	Core™ 2 Quad Q6600 (2.4GHz)		
<b>Memory</b>			
	2GB DDR2		
	4GB DDR2		
	8GB DDR2		
<b>Drive Bay 1, 2, 3</b>		1	2 3
<b>Front accessible 5.25"</b>	No		
	SATA 250 GB		
	SATA 500 GB		
	SATA 750 GB		
	SATA 1TB		
	KISS-Stor 1 (2* 250 GB) (blocks two 5.25" Bays)		
	KISS-Stor 1 (2* 500 GB) (blocks two 5.25" Bays)		
	KISS-Stor 1 (2* 750 GB) (blocks two 5.25" Bays)		
	KISS-Stor 1 (2* 1TB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 250 GB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 500 GB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 750 GB) (blocks two 5.25" Bays)		
	KISS-Stor 0/5 (3* 1TB) (blocks two 5.25" Bays)		
	DVD ROM SATA		
	DVD -R/RW SATA		
<b>Drive Bay 4</b>		4	
<b>Internal 3.5"</b>	No		
	SATA 250 GB		
	SATA 500 GB		
	SATA 750 GB		
	SATA 1TB		
	Slim-line CD-R/RW DVD-ROM		
<b>Power Supply</b>			
	AC 275W (115/230VAC)		
<b>Graphic Adapter</b>			
	No		
	PCIe *16 GEF NX8500GT-TD256EH/D2		
<b>Network Adapter</b>			
	No		
	PCI NET D-LINK DFE-528TX 10/100Mbps		
<b>Options</b>			
	No		
	Custom Color		
	others on request		
<b>Preinstalled OS</b>			
	No		
	Windows XP Multilingual		
	Linux Suse		
	WIN 2003 Server		
	Others on request		
<b>Variant</b>			
	Desktop		
	19" Rack Mount		