



KISS 2U Short Systems

Configuration Guides

Configuration Options for KISS 2U Short 986LCD-M/mITX	
Categories	Select one of each categor
Mainboard	986LCD-M/mITX (2* PCI 32-Bit/33MHz via riser card)
Processor	Celeron M 440 (1.86GHz) Core™ Duo T2500 (2.0 GHz) Core™ 2 Duo T7400 (2.16GHz)
Memory	2 GB DDR2 4 GB DDR2 (3.5 GB available for OS)
Drive Bay 1	No DVD RW SATA REM HDD SATA 500 GB REM HDD SATA 1TB REM HDD SATA 2TB KISS Stor1 Slim [RAID 1 (2* 160 GB HDD)] KISS Stor1 Slim [RAID 1 (2* 250 GB HDD)] KISS Stor1 Slim [RAID 1 (2* 500 GB HDD)]
Drive Bay 2	
Internal 3.5" or front accessible	No SATA HDD 500 GB SATA HDD 1TB SATA HDD 2TB DVD RW SATA (only in configuration with KISS Stor1 Slim in Drive Bay 1) CF Reader SATA
Power Supply	AC, 400W, 80+
Network Adapter	No PCI NET D-LINK DFE-528TX 10/100Mbps
Graphic Adapter	No PCI MATROX G550DH 32MB LP DVI
Options	No Custom Color Slide Rails EASY 485/422 (Adapter RS232 to RS422 or RS485) PCCM [PC Condition Monitoring] (with Windows XP only) others on request
Preinstalled OS	No Windows XP Multilingual Linux Suse Others on request
Variant	Desktop 19" Rack Mount

Configuration Options for KISS 2U Short with KT965 Flex	
Categories	Select one of each categor
Mainboard	KT965 Flex (2* PCI 32-Bit/33MHz via riser card)
Processor	Core™ 2 Duo E4300 (1.8GHz) Core™ 2 Duo E6400 (2.13GHz)
Memory	4 GB DDR2 8 GB DDR2
Drive Bay 1	
Front accessible 5.25"	No DVD RW SATA REM HDD SATA 500 GB REM HDD SATA 1TB REM HDD SATA 2TB KISS Stor1 Slim [RAID 1 (2* 160 GB HDD)] KISS Stor1 Slim [RAID 1 (2* 250 GB HDD)] KISS Stor1 Slim [RAID 1 (2* 500 GB HDD)]
Drive Bay 2	
Internal 3.5" or front accessible	No SATA HDD 500 GB SATA HDD 1TB SATA HDD 2TB DVD -R/RW SATA (only in configuration with KISS Stor1 Slim in Drive Bay 1) CF Reader SATA
Power Supply	AC, 400W, 80+
Network Adapter	No PCI NET D-LINK DFE-528TX 10/100Mbps
Graphic Adapter	No PCI MATROX G550DH 32MB LP DVI
Options	No Custom Color Slide Rails EASY 485/422 (Adapter RS232 to RS422 or RS485) PCCM [PC Condition Monitoring] (with Windows XP only) others on request
Preinstalled OS	No Windows XP Multilingual Linux Suse Others on request
Variant	Desktop 19" Rack Mount

Configuration Options for KISS 2U Short KTQ45/Flex	
Categories	Select one of each categor
Mainboard	KTQ45/Flex
Expansion Slots	2* PCI 32 Bit , optional 1* PCIe x16, 1* PCIe x4 , optional 1* PCI , 1* PCIe
Processor	Core™ 2 Duo E8400 (3GHz) Core™ 2 Quad Q9400 (2.66GHz)
Memory	4 GB DDR3 8 GB DDR3
Drive Bay 1	
Front accessible 5.25"	No DVD RW SATA REM HDD SATA 500 GB REM HDD SATA 1TB REM HDD SATA 2TB KISS Stor1 Slim [RAID 1 (2* 160 GB HDD)] KISS Stor1 Slim [RAID 1 (2* 250 GB HDD)] KISS Stor1 Slim [RAID 1 (2* 500 GB HDD)] DA425 4* 500 GB
Drive Bay 2	
Internal 3.5" or front accessible	No SATA HDD 500 GB SATA HDD 1TB SATA HDD 2TB DVD RW Slim (front accessible) CF Reader SATA (front accessible)
Power Supply	AC, 400W, 80+ others on request
Network Adapter	No PCIe x1, 1 GB LAN, LP, Intel EXPI9301CTBLK
Graphic Adapter	No PCIe x16 Graphic card, passive, LP: NVIDIA Quadro NVS 295 x16 for D\
Options	No Custom Color Slide Rails EASY 485/422 (Adapter RS232 to RS422 or RS485 PCCM [PC Condition Monitoring] (with Windows XP only Others on request
Preinstalled OS	No Windows XP Multilingual Linux Suse WIN 7 32 bit Pro Others on request
Variant	Desktop 19" Rack Mount

Configuration Options for KISS 2U Short with KTQ45/Flex (Low Profile)	
Categories	Select one of each categor
Mainboard	KTQ45/Flex
Expansion Slots	2* PCI 32-Bit, 1* PCIe x16, 1* PCIe x4 (only with Low Profile cards)
Processor	Core™ 2 Duo E8400 (3GHz) Core™ 2 Quad Q9400 (2.66GHz)
Memory	4 GB DDR3 8 GB DDR3
Drive Bay 1	
Front accessible 5.25"	No DVD RW SATA REM HDD SATA 500 GB REM HDD SATA 1TB REM HDD SATA 2TB KISS Stor1 Slim [RAID 1 (2* 160 GB HDD)] KISS Stor1 Slim [RAID 1 (2* 250 GB HDD)] KISS Stor1 Slim [RAID 1 (2* 500 GB HDD)] DA425 4* 500 GB
Drive Bay 2	
Internal 3.5"	No SATA HDD 500 GB SATA HDD 1TB SATA HDD 2TB DVD RW Slim (front accessible) CF Reader SATA (front accessible)
Power Supply	AC, 400W, 80+
Network Adapter	No PCIe x1, 1 GB LAN, LP, Intel EXPI9301CTBLK
Graphic Adapter	No PCIe x16, Graphic card, passive, LP: NVIDIA Quadro NVS 295 x16 for DV
Options	No Custom Color Slide Rails EASY 485/422 (Adapter RS232 to RS422 or RS485) PCCM [PC Condition Monitoring] (with Windows XP only others on request
Preinstalled OS	No Windows XP Multilingual Linux Suse WIN 7 32 bit Pro Others on request
Variant	Desktop 19" Rack Mount