



Kontron's industrial servers and workstations are designed and tested for challenging environments and are therefore the perfect fit for extreme temperature and mechanical stress conditions.

Kontron's desktop server is tailored for use at the interface of IT and OT, handling huge amounts of data.



▶ **ZINC19 2U/4U**
Scalable Rackmount Systems for Challenging and Noise Sensitive Environments

- ▶ Industrial grade for challenging environments – robust, reliable and sustainable
- ▶ High processing capability with 7th Gen Intel® Core™ i3/i5/i7 or Xeon® E3
- ▶ Low noise level
- ▶ Modular concept for easy customization



▶ **HPW 410**
High Performance Workstation/Embedded Server

- ▶ Industrial grade for challenging environments – robust, reliable and sustainable
- ▶ Single or dual Intel® Xeon® E5 for high performance applications
- ▶ Up to 3 high performance GPGPUs for extensive graphics applications
- ▶ Low noise level
- ▶ Modular concept for easy customization



▶ **ZINC CUBE C232**
Embedded Server Platform for High Performance and Cloud Computing

- ▶ Compact desktop server with excellent performance and extended storage functions
- ▶ High processing capability with 7th Gen Intel® Core™ i7/i5/i3 or XEON® E3
- ▶ Qualified for Windows and Linux Server OS

About Kontron – An S&T Company

Kontron is a global leader in IoT/embedded computing technology (ECT). As a part of technology group S&T, Kontron offers a combined portfolio of secure hardware, middleware and services for Internet of Things (IoT) and Industry 4.0 applications. With its standard products and tailor-made solutions based on highly reliable state-of-the-art embedded technologies, Kontron provides secure and innovative applications for a variety of industries. As a result, customers benefit from accelerated time-to-market, reduced total cost of ownership, product longevity and the best fully integrated applications overall.

About the Intel® Internet of Things Solutions Alliance

From modular components to market-ready systems, Intel and the 400+ global member companies of the Intel® Internet of Things Solutions Alliance provide scalable, interoperable solutions that accelerate deployment of intelligent devices and end-to-end analytics. Close collaboration with Intel and each other enables Alliance members to innovate with the latest IoT technologies, helping developers deliver first-in-market solutions.



Global Headquarters

Kontron S&T AG

Lise-Meitner-Str. 3-5
86156 Augsburg, Germany
Tel.: +49 821 4086-0
Fax: +49 821 4086-111
info@kontron.com

www.kontron.com

Industrial Applications
**SERVERS /
WORKSTATIONS**



- ▶ **INDUSTRIAL GRADE**
Perfect fit for challenging and rough environments
- ▶ **HIGH PERFORMANCE COMPUTING**
High processing capability and graphics power
- ▶ **EASY CUSTOMIZATION**
Modular and flexible concept

Copyright © 2018 Kontron AG. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate. However, the company is not liable for any errors or omissions. Kontron, the Kontron logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized. Specifications are subject to change without notice. T55ackmount-20171122-WMH

SERVERS / WORKSTATIONS

FOR INDUSTRIAL APPLICATIONS & CLOUD COMPUTING



ZINC19 2U



ZINC19 4U



HPW 410



ZINC CUBE C232



CHIPSET	Intel® C236	Intel® C236
PROCESSOR	7th Gen Intel® Core™ or XEON® E3-1200 v6 series: E3-1275 v6, i3-7101T(E), i5-7500(T), i7-7700(T) 6th Gen Intel® Core™ or XEON® E3-1200 v5 series: E3-1225 v5, E3-1275 v5, i3-6100TE, i5-6500TE, i7-6700	7th Gen Intel® Core™ or XEON® E3-1200 v6 series: E3-1275 v6, i3-7101T(E), i5-7500(T), i7-7700(T) 6th Gen Intel® Core™ or XEON® E3-1200 v5 series: E3-1225 v5, E3-1275 v5, i3-6100TE, i5-6500TE, i7-6700
MEMORY	16 GByte DDR4 32 GByte DDR4 64 GByte DDR4 ECC (Intel® XEON® & i3 only)	16 GByte DDR4 32 GByte DDR4 64 GByte DDR4 ECC (Intel® XEON® & i3 only)
STANDARD IOS	Front: 2x USB 2.0 Rear: 4x USB 3.0, 2x USB 2.0, 1x LAN, 2x RS232, Audio, 1x DVI-D, 2x DP, 2x PS/2	Front: 2x USB 3.0 Rear: 4x USB 3.0, 4x USB 2.0, 2x LAN, 1x RS232, Audio, 1x DVI-D, 2x DP, 2x PS/2
EXPANSION SLOTS	2x PCIe x16, 2x PCIe x1	2x PCIe x16, 1x PCIe x8, 2x PCIe x4, 2x PCI
PSU	100-240 V AC	100-240 V AC
DRIVE OPTIONS	SSD 128 GB, 256 GB, 512 GB, 1 TB HDD 1 TB, 2 TB, 4 TB, 6 TB PCIe SSD 400 GB, 800 GB, 1.2 TB DVD R/W	SSD 128 GB, 256 GB, 1 TB HDD 1 TB, 2 TB, 4 TB, 6 TB PCIe SSD 400 GB, 800 GB, 1.2 TB DVD R/W
CERTIFICATIONS	CE, designed for UL	CE, designed for UL
NON OPERATING	-20 °C to +70 °C	-20 °C to +70 °C
OPERATING	0 °C to +50 °C	0 °C to +50 °C
SHOCK	15 g, 11 ms	15 g, 11 ms
VIBRATION	1 g 10-150 Hz	1 g 10-150 Hz
ALTITUDE	3000 m	3000 m
VERIFIED OS	Windows 7 (6th Gen Intel® Core™ or XEON® E3-1200 v5 series), Windows 10, Linux	Windows 7 (6th Gen Intel® Core™ or XEON® E3-1200 v5 series), Windows 10, Linux

CHIPSET	Intel® C612	Intel® C232
PROCESSOR	Single or dual Intel® XEON® E5-2600 v4 series: E5-2620 v4, E5-2640 v4, E5-2680 v4	7th Gen Intel® Core™ or XEON® E3-1200 v6 series: E3-1275 v6, i3-7101T(E), i5-7500(T), i7-7700(T)
MEMORY	Up to 128 GByte (all per processor) 16 GByte DDR4 32 GByte DDR4 64 GByte DDR4 96 GByte DDR4 128 GByte DDR4	8 GByte DDR4 16 GByte DDR4 ECC (Intel® XEON® & i3 only)
STANDARD IOS	Front: 2x USB 3.0 Rear: Single CPU: 2x USB 3.0, 4x USB 2.0, 2x LAN, 1x Audio, RS232 (optional) Dual CPU: 2x USB 3.0, 2x USB 2.0, 2x LAN, 1x, 1x VGA, RS232 (optional)	Front: 2x USB 3.0 Rear: 2x USB 3.0, 2x USB 2.0, 2x LAN, 1x VGA
EXPANSION SLOTS	Single CPU: 2x PCIe x1, 3x PCIe x4, 2x PCIe x16 Dual CPU: 1x PCIe x4, 1x PCIe x8, 4x PCIe x16	1x PCIe x16 (Low Profile)
PSU	100-240 V AC	100-240 V AC
DRIVE OPTIONS	SSD 128 GB HDD 2 TB, 4 TB, 6 TB DVD R/W	2x 2.5" SSD/HDD removable 2x 3.5" SSD/HDD removable 1x M.2 2280
CERTIFICATIONS	CE, designed for UL	CE, designed for UL
NON OPERATING	-20 °C to +70 °C	-20 °C to +70 °C
OPERATING	0 °C to +50 °C	0 °C to +35 °C
SHOCK	15 g, 11 ms	tbd
VIBRATION	1 g 10-150 Hz	tbd
ALTITUDE	3000 m	tbd
VERIFIED OS	Windows 7 (Single CPU), Windows 10, Windows Server 2012 R2, Red Hat Linux	Windows 10 (64bit), Windows Server (64bit), Linux Server (64bit)

